

**DEWALT**

WHERE SIZE MEETS POWER™

DCG432XB ATOMIC™ 20V MAX* 4 IN. EXTENDED CUT-OFF TOOL

Make straight, clean cuts in tight or narrow spaces with the industry's first battery-operated 4 in. extended cut-off tool. The ATOMIC™ 20V MAX* 4 in. Extended Cut-Off Tool (battery and charger sold separately) is engineered for tough metalworking applications and is equipped with the DEWALT® ANTI-ROTATION System to help maximize control. For convenience, the ATOMIC™ 20V MAX* 4 in. Extended Cut-Off Tool is designed with a rotating guard that offers 11 positions and helps to optimize cuts in a wide range of angles. This tool delivers comparable power vs. 0.9 HP rated pneumatic 4 in. extended cut off tools***. At 28% lighter than competitive pneumatic 4 in. extended cut-off tool in use[†], this cordless solution delivers pneumatic-like power without the hassle of hoses.

20V MAX*™**ATOMIC**
COMPACT SERIES™

* - Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

*** - Based on MWO, using DCBP320 battery (sold separately).

† - On average, measured with DCBP034G battery (sold separately) vs. Dynabrade ECU4 with 36" of connected 1/2" diameter hose and equal accessories. Dynabrade® is a trademark of Dynabrade, Inc., which has not endorsed, approved, or sponsored this comparison.

DCG432XBSS

ATOMIC™ 20V MAX* 4 IN. EXTENDED CUT-OFF TOOL

ERGONOMIC DESIGN

44% smaller gearcase height*

TOOL-FREE ADJUSTMENTS

Work comfortably in tight or awkward spaces with rotation adjustments up to +/- 75 degrees

HELP MAXIMIZE CONTROL

Equipped with the DEWALT® ANTI-ROTATION System

FORWARD EXHAUST SYSTEM

Help direct air away from the user

FORWARD/REVERSE FUNCTIONALITY

Seamlessly switch directions

SPINDLE LOCK

Removes the need for multiple wrenches

ROTATING GUARD

11 positions for a wide range of applications

BRAKE STOPS WHEEL WITHIN 1.1 SECONDS††

Help maintain control after the on/off trigger is released

PADDLE SWITCH

Lock-off paddle and no lock-on

TOOL CONNECT™ CHIP READY™

Pair with the TOOL CONNECT™ Chip (Sold Separately) and TOOL CONNECT™ software‡



Ergonomic Design - Complete metalworking applications in tight or narrow spaces with a 44% smaller gearcase height*

** Based on using DCBP034 battery (sold separately)

†† - On average, using 1/8" T1 DW8718 wheel.

‡ - Vs. DCG408 Angle Grinder.

§ - Additional subscription charge and third party data charges may apply.

SPECIFICATION

NO LOAD SPEED	12,500 RPM**
MAX WATTS OUT	640W**
TOOL WEIGHT	3.21 lbs
VARIABLE SPEED	No
FORWARD/REVERSE	Yes
LED	Yes
SPINDLE LOCK	Yes
LOCK-ON SWITCH	No
MAX ACCESSORY DIAMETER	3/8 in.
CONNECTIVITY	TOOL CONNECT™ CHIP READY™ (DEWALT® Chip Sold Separately)

WARRANTY

TOOL WARRANTY

3
YEAR

LIMITED WARRANTY

1
YEAR

FREE SERVICE

90
DAY

MONEY BACK GUARANTEE

PRODUCT OFFERINGS

DCG432XGE2

- (1) DCG432X 4 in. Extended Cut-Off Tool
- (2) DCBP034G 20V MAX* XR POWERSTACK™ 1.7Ah Oil Resistant Batteries
- (1) Charger
- (1) Type 1 Cutting Wheel
- (1) Inner and Outer Flange
- (1) Wrench
- (1) Accessory Bolt
- (1) Kit Bag



RELATED PRODUCTS

DCG430B

ATOMIC™ 20V MAX* 3 in. Cut-Off Tool (Tool Only)



DCG420XB

ATOMIC™ 20V MAX* Extended Die Grinder (Tool Only)

